

U.S.S.N. 10/562,662

-12-

GKNG 1272 PCT

IN THE ABSTRACT:

On page 45 and continuing on page 46 of the English Language translation of the specification, please amend the Abstract of the specification to appear as follows:

~~The invention relates to a longitudinal plunging unit 24 for a shaft assembly for transmitting torque. The A longitudinal plunging unit comprises a profiled sleeve 25 with circumferentially distributed, longitudinally extending first ball grooves, and 26; a profiled journal [[1]] with circumferentially distributed, longitudinally extending second ball grooves, 6, wherein the The profiled journal 1, by means of its end 2 facing the profiled sleeve 26, engages said profiled sleeve 25; with balls 44 arranged in groups in pairs of first ball groove 26 and second ball grooves, 6; and a A ball cage 40 which, in the radial direction, is positioned between the profiled sleeve 25 and the profiled journal 1 and fixes the balls 44 in their axial position relative to one another. The ball cage 40 is displaceable relative to the profiled journal [[1]] between spaced axial stops. On the profiled journal [[1]], there is arranged a stop sleeve 43, which can abut the profiled journal [[1]] or a component connected thereto. The stop sleeve 43 delimits the displacement path of the ball cage 40 towards the second portion.~~

~~Figure 1~~